

## Firestone



Hints and features:

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- · Long service life and even wear.

AST-TYRE 420 / 85 R 24 142 A8 / 142 B, TL, PERFORMER XL (16.9 R 24)

Product-No.: 10626156

## **Technical Information:**

Product number	10626156
Tyre Size	420 / 85 R 24
R/D	Radial
TL / TT	TL
LI/SI	142 A8 / 142 B
Tread	Performer 85 XL
Manufacturer	Firestone
Recom. Rim	15
Permissible rim	14
Width mm	446
Outer diameter mm	1323
Static radius mm	596
Rolling circumference mm	3996
Payload in kg at kph (1)	2650 / 40
Payload in kg at kph (2)	2650 / 50
Inflation pressure bar	2,40
Weight kg	96,68
Tyre content 75% litre	238.5
Stud height mm	44,0
Number of studs	19x2
Certified	nicht notwendig
Nominal width [mm]	420
Aspect ratio	85
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.