# Bohnenkamp Moving Professionals

## Firestone



#### Hints and features:

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.
- · Long service life and even wear

# AST-TYRE 340 / 85 R 28 127 D / 124 E, TL, PERFORMER (13.6 R 28)

# Product-No.: 10626256

### **Technical Information:**

Product number	10626256
Tyre Size	340 / 85 R 28
R / D	Radial
TL / TT	TL
LI / SI	127 D / 124 E
Tread	Performer 85
Manufacturer	Firestone
Recom. Rim	12
Permissible rim	11
Width mm	354
Outer diameter mm	1302
Static radius mm	585
Rolling circumference mm	3906
Payload in kg at kph (1)	1750 / 65
Payload in kg at kph (2)	1600 / 70
Inflation pressure bar	1,60
Weight kg	64,5
Tyre content 75% litre	157.5
Stud height mm	41,0
Number of studs	20x2
Certified	nicht notwendig
Nominal width [mm]	340
Aspect ratio	85
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.