

Firestone



Hints and features:

- Narrow tyre for maintenance of row crops.
- · High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- · Long service life.
- · Long service life and even wear

AST-TYRE 320 / 85 R 36 128 D / 125 E, TL, PERFORMER (12.4 R 36)

Product-No.: 10626381

Technical Information:

Product number	10626381
Tyre Size	320 / 85 R 36
R/D	Radial
TL/TT	TL
LI / SI	128 D / 125 E
Tread	Performer 85
Manufacturer	Firestone
Recom. Rim	11
Permissible rim	9, 10
Width mm	321
Outer diameter mm	1459
Static radius mm	654
Rolling circumference mm	4377
Payload in kg at kph (1)	1800 / 65
Payload in kg at kph (2)	1650 / 70
Inflation pressure bar	1,60
Weight kg	70,8
Tyre content 75% litre	156
Stud height mm	43,0
Number of studs	23x2
Certified	nicht notwendig
Nominal width [mm]	320
Aspect ratio	85
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.