Bohnenkamp Moving Professionals

Firestone



Hints and features:

- Unique double-angle lug technology.
- Large ground contact area due to stronger deflection and flatter tread pattern contour.
- Increased ride comfort.

AST-TYRE 480 / 70 R 24 138 D/135 E, TL, PERFORMER Firestone

Product-No.: 10626645

Technical Information:

Product number	10626645
Tyre Size	480 / 70 R 24
R / D	Radial
TL / TT	TL
LI / SI	138 D / 135 E
Tread	Performer 70
Manufacturer	Firestone
Recom. Rim	15
Permissible rim	14, 16
Width mm	482
Outer diameter mm	1323
Static radius mm	595
Rolling circumference mm	3969
Payload in kg at kph (1)	2360 / 65
Payload in kg at kph (2)	2180 / 70
Inflation pressure bar	1,60
Weight kg	98,8
Tyre content 75% litre	264
Stud height mm	46,5
Number of studs	18x2
Certified	nicht notwendig
Nominal width [mm]	480
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.