





Hints and features:

- The AC 90 is a modern row crop tyre for driving on row crops.
- The rounded lugs and lug shoulders effectively protect crops.
- The tyre is characterised by its excellent traction, high load capacity as well as excellent ride comfort at speeds up to 50 km/h.

AST-TYRE 270 / 95 R 48 144 A8 / 141 B, TL, AC 90 MITAS Mitas

Product-No.: 10926494

Technical Information:

Product number	10926494
Tyre Size	270 / 95 R 48
R/D	Radial
TL/TT	TL
LI/SI	144 A8 / 141 B
Tread	AC 90
Manufacturer	Mitas
Recom. Rim	9
Permissible rim	W8, W10
Width mm	287
Outer diameter mm	1737
Static radius mm	810
Rolling circumference mm	5220
Payload in kg at kph (1)	2800 / 40
Payload in kg at kph (2)	2575 / 50
Inflation pressure bar	4,00
Weight kg	76,8
Stud width mm	29
Stud height mm	33,0
Number of studs	30x2
Certified	nicht notwendig
Nominal width [mm]	270
Aspect ratio	95
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.