



#### Hints and features:

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

IMPLEMENT TYRE (FOR TRAILERS) 650 / 65 R 30.5"  
176 D, TL, FLOTATION 380  
STEEL BELTED

**Product-No.: 15215793**

#### Technical Information:

Product number	15215793
Tyre Size	650 / 65 R 30.5
R / D	Radial
TL / TT	TL
LI / SI	176 D
Tread	380
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	20.00
Width mm	680
Outer diameter mm	1625
Static radius mm	726
Rolling circumference mm	4881
Payload in kg at kph (1)	7100 / 65
Inflation pressure bar	4,00
Weight kg	200,27
Tyre content 75% litre	579
Stud height mm	26,0
Certified	ECE 106
Nominal width [mm]	650
Aspect ratio	65
Tread symmetry	symmetrisch