



AST-TYRE 520 / 85 R 42
157 A8 / 157 B , TL, RT 855 AS
(20.8 R 42)

Product-No.: 15726430

Technical Information:

Product number	15726430
Tyre Size	520 / 85 R 42
R / D	Radial
TL / TT	TL
LI / SI	157 A8 / 157 B
Tread	Agrimax RT 855
Manufacturer	BKT
Recom. Rim	DW16L
Permissible rim	W16A, DD16, DW18A, DD18, W18A, DD18L
Width mm	516
Outer diameter mm	1951
Static radius mm	858
Rolling circumference mm	5782
Payload in kg at kph (1)	4125 / 40
Payload in kg at kph (2)	4125 / 50
Inflation pressure bar	1,60
Weight kg	196,84
Tyre content 75% litre	547.5
Stud width mm	45
Stud height mm	57,0
Number of studs	22x2
Certified	ECE 106
Nominal width [mm]	520
Aspect ratio	85
Direction bound	Yes
Tread symmetry	symmetrisch

Hints and features:

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.