# Bohnenkamp Moving Professionals



### Hints and features:

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

# AST-TYRE 320 / 70 R 20 123 A8 / 123 B, TL, RT 765 AS BKT

# Product-No.: 15726590

## **Technical Information:**

Product number	15726590
Tyre Size	320 / 70 R 20
R / D	Radial
TL/TT	TL
LI / SI	123 A8 / 123 B
Tread	Agrimax RT 765
Manufacturer	ВКТ
Recom. Rim	W10
Permissible rim	W9, W11
Width mm	319
Outer diameter mm	982
Static radius mm	445
Rolling circumference mm	2938
Payload in kg at kph (1)	1550 / 40
Payload in kg at kph (2)	1550 / 50
Inflation pressure bar	2,40
Weight kg	38,9
Tyre content 75% litre	78.75
Stud width mm	28
Stud height mm	33,0
Number of studs	17x2
Certified	ECE 106
Nominal width [mm]	320
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.