



AST-TYRE 380 / 70 R 20
132 A8 / 132 B, TL, RT 765 AS
BKT

Product-No.: 15726602

Technical Information:

Product number	15726602
Tyre Size	380 / 70 R 20
R / D	Radial
TL / TT	TL
LI / SI	132 A8 / 132 B
Tread	Agrimax RT 765
Manufacturer	BKT
Recom. Rim	W12
Permissible rim	W11, W13
Width mm	380
Outer diameter mm	1082
Static radius mm	482
Rolling circumference mm	3213
Payload in kg at kph (1)	2000 / 40
Payload in kg at kph (2)	2000 / 50
Inflation pressure bar	2,40
Weight kg	59,8
Tyre content 75% litre	123.75
Stud width mm	32
Stud height mm	42,0
Number of studs	17x2
Certified	ECE 106
Nominal width [mm]	380
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

Hints and features:

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.