



AST-TYRE 620 / 75 R 26 166 A8 / 166 B, TL, AGRIMAX TERIS BKT

Product-No.: 15726660

Technical Information:

Product number	15726660
Tyre Size	620 / 75 R 26 CHO
R / D	Radial
TL / TT	TL
LI / SI	166 A8 / 166 B
Tread	Agrimax Teris
Manufacturer	BKT
Recom. Rim	DW20B
Width mm	625
Outer diameter mm	1590
Static radius mm	730
Rolling circumference mm	4851
Payload in kg at kph (1)	5300 / 40
Payload in kg at kph (2)	5300 / 50
Inflation pressure bar	3,20
Weight kg	203
Tyre content 75% litre	542.25
Stud height mm	50,0
Number of studs	19x2
Certified	ECE 106
Cyclic field use	CHO
Nominal width [mm]	620
Aspect ratio	75
Direction bound	Yes
Tread symmetry	symmetrisch

Hints and features:

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.