# Bohnenkamp Moving Professionals

## BKT



#### Hints and features:

- Super-volume tyre for harvesters, selfpropelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

## AST-TYRE 620 / 75 R 30 168 A8 / 168 B, TL, AGRIMAX TERIS BKT

## Product-No.: 15726795

### **Technical Information:**

Product number	15726795
Tyre Size	620 / 75 R 30 CHO
R / D	Radial
TL / TT	TL
LI / SI	168 A8 / 168 B
Tread	Agrimax Teris
Manufacturer	ВКТ
Recom. Rim	DW20B
Width mm	625
Outer diameter mm	1692
Static radius mm	779
Rolling circumference mm	5169
Payload in kg at kph (1)	5600 / 40
Payload in kg at kph (2)	5600 / 50
Inflation pressure bar	3,20
Weight kg	219
Tyre content 75% litre	558.64
Stud height mm	50,0
Number of studs	20x2
Certified	ECE 106
Cyclic field use	СНО
Nominal width [mm]	620
Aspect ratio	75
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.