Bohnenkamp Moving Professionals

nokicin[®] TYRES



Hints and features:

- Ideal in the most varying conditions, reliable throughout the whole year.
- High level of directional stability in onroad and off-road applications.
- The tread pattern ensures rapid selfcleaning for a clean road surface.
- Designed for exceptional durability.
- Environmentally friendly: manufactured without polluting aromatic oils. Exemplary low rolling resistance reduces fuel consumption.

AST-TYRE 340 / 80 R 18 138 D, TL, TRI 2 (12.5 R 18)

Product-No.: 17426010

Technical Information:

| Product number | 17426010 |
|--------------------------|-----------------|
| Tyre Size | 340 / 80 R 18 |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 143 A8 / 138 D |
| Tread | TRI 2 |
| Manufacturer | Nokian |
| Specification | M+S |
| Recom. Rim | 11 |
| Permissible rim | 10, 12 |
| Width mm | 343 |
| Outer diameter mm | 1001 |
| Static radius mm | 453 |
| Rolling circumference mm | 3010 |
| Payload in kg at kph (1) | 2725 / 40 |
| Payload in kg at kph (2) | 2360 / 65 |
| Inflation pressure bar | 4,00 |
| Weight kg | 54,8 |
| Tyre content 75% litre | 110 |
| Stud height mm | 25,0 |
| Certified | nicht notwendig |
| M+S | M+S |
| Nominal width [mm] | 340 |
| Aspect ratio | 80 |
| Direction bound | Yes |
| Tread symmetry | asymmetrisch |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.