



Reifen IF 380 / 95 R 38, Agriflex 354
154 D, TL, Steel Belted
Alliance

Product-No.: 15227328

Technical Information:

Product number	15227328
Tyre Size	IF 380 / 95 R 38
R / D	Radial
TL / TT	TL
LI / SI	154 D
Tread	Agriflex 354
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	13
Permissible rim	12
Width mm	390
Outer diameter mm	1687
Static radius mm	767
Rolling circumference mm	5018
Payload in kg at kph (1)	3750 / 65
Inflation pressure bar	2,40
Weight kg	128,86
Tyre content 75% litre	270
Stud height mm	48,0
Number of studs	30x2
Certified	ECE 106
Nominal width [mm]	380
Aspect ratio	95
Tyre technology	IF
Direction bound	Yes
Tread symmetry	symmetrisch

Hints and features:

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers.
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.