Bohnenkamp Moving Professionals

KENDA



Hints and features:

- Versatile traction tyre.
- Ideal for use on compact tractors and single-axle tractors.

Reifen 16 x 6.50 - 8, K357 4 PR, 52 A4 / 63 A4, TL AS, Kenda

Product-No.: 19211177

Technical Information:

Product number	19211177
Tyre Size	16 x 6.50 - 8
R / D	Diagonal
TL / TT	TL
LI / SI	52 A4 / 63 A4
PR	4
Tread	K357
Manufacturer	Kenda
Recom. Rim	5.3751
Width mm	163
Outer diameter mm	425
Rolling circumference mm	1268
Payload in kg at kph (1)	200 / 20
Payload in kg at kph (2)	272 / 20
Inflation pressure bar	1,90
Weight kg	3,43
Certified	ECE 106
Nominal width [inch]	6.50
Nominal diameter [inch]	16
Direction bound	Yes
Tread symmetry	asymmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.