



Hints and features:

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.

AST-TYRE 480 / 70 R 28
151 A8 / 145 E, TL, AS 370
HIGH SPEED

Product-No.: 15225112

Technical Information:

Product number	15225112
Tyre Size	480 / 70 R 28
R / D	Radial
TL / TT	TL
LI / SI	151 A8 / 145 E
Tread	370
Manufacturer	Alliance
Specification	High Speed
Recom. Rim	15
Permissible rim	14, 16
Width mm	479
Outer diameter mm	1423
Static radius mm	640
Rolling circumference mm	4313
Payload in kg at kph (1)	3450 / 40
Payload in kg at kph (2)	2900 / 70
Inflation pressure bar	2,50
Weight kg	106,82
Tyre content 75% litre	288
Stud width mm	37
Stud height mm	46,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	480
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch