



Hints and features:

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- · Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

AST-TYRE 270/ 95 R 36 139 A8 / 139 B, TL, RT 955 AGRIMAX (11.2 R 36)

Product-No.: 15727465

Technical Information:

Product number	15727465
Tyre Size	270 / 95 R 36
R/D	Radial
TL/TT	TL
LI/SI	139 A8 / 139 B
Tread	Agrimax RT 955
Manufacturer	вкт
Recom. Rim	W9
Permissible rim	W8, W10
Width mm	275
Outer diameter mm	1428
Static radius mm	665
Rolling circumference mm	4368
Payload in kg at kph (1)	2430 / 40
Payload in kg at kph (2)	2430 / 50
Inflation pressure bar	4,00
Weight kg	60,54
Stud width mm	27
Stud height mm	35,0
Number of studs	25x2
Certified	ECE 106
Nominal width [mm]	270
Aspect ratio	95
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.