## Bohnenkamp Moving Professionals

BKT



## Hints and features:

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

Reifen 360 / 80 R 24, Ridemax IT 696 143 A8 / 138 D, TL (13.6R24), BKT

## Product-No.: 15775032

## **Technical Information:**

Product number	15775032
Tyre Size	360 / 80 R 24
R / D	Radial
TL / TT	TL
LI / SI	143 A8 / 138 D
Tread	Ridemax IT 696
Manufacturer	ВКТ
Recom. Rim	DW11
Permissible rim	W12, W10
Width mm	343
Outer diameter mm	1186
Static radius mm	537
Rolling circumference mm	3556
Payload in kg at kph (1)	2725 / 40
Payload in kg at kph (2)	2360 / 65
Inflation pressure bar	3,20
Weight kg	67,6
Stud height mm	25,0
Certified	ECE 106
Nominal width [mm]	360
Aspect ratio	80

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.