



Bohnenkamp



Hints and features:

- The Vredestein Flotation Pro is a radial tyre for agricultural trailers.
- The tread pattern is reinforced by a sturdy belt and provides excellent soil protection as well as good ride comfort in difficult ground conditions.
- The tyre is approved for up to 65 km/h and thus optimally suited to road use as well.

Reifen 560 / 45 R 22.5, FLOTATION PRO 152 D, TL Vredestein

Product-No.: 14815152

Technical Information:

Product number	14815152
Tyre Size	560 / 45 R 22.5
R/D	Radial
TL/TT	TL
LI/SI	152 D
Tread	FLOTATION PRO
Manufacturer	Vredestein
Recom. Rim	16.00
Width mm	545
Outer diameter mm	1085
Static radius mm	490
Rolling circumference mm	3295
Rolling circumference mm Payload in kg at kph (1)	3295 3550 / 65
-	
Payload in kg at kph (1)	3550 / 65
Payload in kg at kph (1) Inflation pressure bar	3550 / 65 4,00
Payload in kg at kph (1) Inflation pressure bar Weight kg	3550 / 65 4,00 91,3
Payload in kg at kph (1) Inflation pressure bar Weight kg Stud height mm	3550 / 65 4,00 91,3 17,0
Payload in kg at kph (1) Inflation pressure bar Weight kg Stud height mm Certified	3550 / 65 4,00 91,3 17,0 ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.