

CARLISLE



Hints and features:

- The Carlisle All Trail was specially designed for use on hard surfaces.
- Its low, wide tread pattern makes the vehicle very stable.
- The uniquely firm tread compound provides a very good ride comfort.
- Its rubber compound makes the tyre very durable and provides outstanding handling characteristics on pavement, concrete and compacted soil.

Reifen 22 x 9.50 - 10, All Trail II
4 PR, 63 F, TL
Carlisle

Product-No.: 12500385

Technical Information:

| | |
|--------------------------|-----------------|
| Product number | 12500385 |
| Tyre Size | 22 x 9.50 - 10 |
| R / D | Diagonal |
| TL / TT | TL |
| LI / SI | 63 F |
| PR | 4 |
| Tread | All Trail II |
| Manufacturer | Carlisle |
| Recom. Rim | 8.00 |
| Width mm | 244 |
| Outer diameter mm | 559 |
| Static radius mm | 249 |
| Rolling circumference mm | 1658 |
| Payload in kg at kph (1) | 272 / 80 |
| Inflation pressure bar | 0,97 |
| Weight kg | 6,8 |
| Stud height mm | 11,0 |
| Certified | nicht notwendig |
| Nominal width [inch] | 9.50 |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.