



Reifen 360 / 70 R 24, Agri Star II
122 D, TL, Stubble Guard
Alliance

Product-No.: 15228825

Technical Information:

Product number	15228825
Tyre Size	360 / 70 R 24
R / D	Radial
TL / TT	TL
LI / SI	122 D
Tread	Agri Star II
Manufacturer	Alliance
Specification	Stubble Guard
Recom. Rim	W11
Permissible rim	W10, W12
Width mm	360
Outer diameter mm	1156
Static radius mm	525
Rolling circumference mm	3400
Payload in kg at kph (1)	1500 / 65
Inflation pressure bar	1,60
Weight kg	59
Tyre content 75% litre	130.65
Stud height mm	42,0
Number of studs	20x2
Certified	ECE 106
Nominal width [mm]	360
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

Hints and features:

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.