





Hints and features:

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and punctureresistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.

Reifen 380 / 70 R 28, Agri Star II 127 D, TL, Stubble Guard Alliance

Product-No.: 15228838

Technical Information:

Product number	15228838
Tyre Size	380 / 70 R 28
R/D	Radial
TL/TT	TL
LI / SI	127 D
Tread	Agri Star II
Manufacturer	Alliance
Specification	Stubble Guard
Recom. Rim	W12
Permissible rim	W11, W13
Width mm	385
Outer diameter mm	1295
Static radius mm	595
Rolling circumference mm	3796
Payload in kg at kph (1)	1750 / 65
Inflation pressure bar	1,60
Weight kg	75
Tyre content 75% litre	173.85
Stud height mm	45,0
Number of studs	21x2
Certified	ECE 106
Nominal width [mm]	380
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.