



Reifen 295 / 80 R 22.5, S815
16 PR, 152 / 148 M, TL, 3PMSF
VA/HA/TR, Sailun

Product-No.: 11066314

Technical Information:

Product number	11066314
Tyre Size	295 / 80 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	152 / 148 M
PR	16
Tread	S815
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	8.25
Width mm	295
Outer diameter mm	1044
Rolling circumference mm	3058
Payload in kg at kph (1)	3550 / 130
Inflation pressure bar	8,50
Weight kg	60,96
Rolling resistance	D
Wet grip	C
Rolling noise DB	73
Rolling noise level	B
Stud height mm	17,0
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	295
Aspect ratio	80
Tread symmetry	symmetrisch

Hints and features:

- The Sailun S815 is a truck tyre for all axles, mainly for use on building sites.
- Zigzag-shaped circumferential grooves provide good traction and prevent stones from penetrating the tyre.
- The deep shoulder groove reduces heat build-up and increases traction.
- Sidewall guards protect the casing from damages.
- The sturdy rubber compound and high tread pattern depth guarantee a long service life for the tyre.