



Reifen 385 / 65 R 22.5, S825
20 PR, 160 K (158 L), TL, 3PMSF
VA/HA/TR, Sailun

Product-No.: 11066375

Technical Information:

Product number	11066375
Tyre Size	385 / 65 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	160 K (158 L)
PR	20
Tread	S825
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	11.75
Width mm	385
Outer diameter mm	1072
Static radius mm	495.96
Rolling circumference mm	3103
Payload in kg at kph (1)	4500 / 110
Payload in kg at kph (2)	4250 / 120
Inflation pressure bar	9,00
Weight kg	77
Rolling resistance	D
Wet grip	B
Rolling noise DB	72
Rolling noise level	B
Stud height mm	16,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	385
Aspect ratio	65
Tread symmetry	symmetrisch

Hints and features:

- The Sailun S825 is a truck tyre for all axles.
- The optimised tread compound increases the tyre's service life.
- Its special shoulder design and the wide tread provide good stability.
- Stone ejectors in the circumferential tread ribs prevent tyre damage caused by the penetration of small stones.

