Bohnenkamp Moving Professionals



Hints and features:

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.

Reifen 600 / 65 R 38, Agristar 365 162 A8 / 159 D, TL Alliance

Product-No.: 15226788

Technical Information:

Product number	15226788
Tyre Size	600 / 65 R 38
R / D	Radial
TL/TT	TL
LI / SI	162 A8 / 159 D
Tread	Agristar 365
Manufacturer	Alliance
Recom. Rim	DW20B
Permissible rim	DW18
Width mm	594
Outer diameter mm	1745
Static radius mm	782
Rolling circumference mm	5284
Payload in kg at kph (1)	4750 / 40
Payload in kg at kph (2)	4375 / 65
Inflation pressure bar	2,40
Weight kg	181,16
Tyre content 75% litre	478
Stud width mm	46-49
Stud height mm	49,0
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	65
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.