

Kleber



■ ■ ■ Bohnenkamp

Reifen 230 / 95 R 40, Cropker
135 A8 / 132 D, TL
(9.5R40), Kleber

Product-No.: 12426785

Technical Information:

Product number	12426785
Tyre Size	230 / 95 R 40
R / D	Radial
TL / TT	TL
LI / SI	135 A8 / 132 D
Tread	Cropker
Manufacturer	Kleber
Recom. Rim	7
Permissible rim	8
Width mm	225
Outer diameter mm	1448
Static radius mm	684
Rolling circumference mm	4350
Payload in kg at kph (1)	2180 / 40
Payload in kg at kph (2)	2000 / 65
Inflation pressure bar	4,00
Weight kg	51
Tyre content 75% litre	92
Stud height mm	36,0
Number of studs	28x2
Certified	nicht notwendig
Nominal width [mm]	230
Aspect ratio	95
Direction bound	Yes
Tread symmetry	symmetrisch

Hints and features:

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.