



Hints and features:

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Reifen 320 / 90 R 46, 350
151 A8 / 148 D, TL
(12.4R46), Alliance

Product-No.: 15226300

Technical Information:

Product number	15226300
Tyre Size	320 / 90 R 46
R / D	Radial
TL / TT	TL
LI / SI	151 A8 / 148 D
Tread	350
Manufacturer	Alliance
Recom. Rim	11
Permissible rim	9, 10
Width mm	315
Outer diameter mm	1727
Static radius mm	807
Rolling circumference mm	5294
Payload in kg at kph (1)	3450 / 40
Payload in kg at kph (2)	3150 / 65
Inflation pressure bar	3,60
Weight kg	83,04
Tyre content 75% litre	201.75
Stud width mm	28
Stud height mm	38,0
Number of studs	30x2
Certified	ECE 106
Nominal width [mm]	320
Aspect ratio	90
Direction bound	Yes
Tread symmetry	symmetrisch