Bohnenkamp Moving Professionals

BKT



Hints and features:

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.

Reifen IF 800 / 70 R 38 CFO, Agrimax Force 184 D, TL BKT

Product-No.: 15726962

Technical Information:

| Product number | 15726962 |
|--------------------------|----------------------|
| Tyre Size | IF 800 / 70 R 38 CFO |
| R / D | Radial |
| TL / TT | TL |
| LI / SI | 184 D |
| Tread | Agrimax Force |
| Manufacturer | ВКТ |
| Recom. Rim | DW27B |
| Permissible rim | DW25B |
| Width mm | 794 |
| Outer diameter mm | 2085 |
| Static radius mm | 923 |
| Rolling circumference mm | 6184 |
| Payload in kg at kph (1) | 9000 / 65 |
| Inflation pressure bar | 2,40 |
| Weight kg | 412,23 |
| Stud height mm | 60,0 |
| Number of studs | 21x2 |
| Certified | ECE 106 |
| Nominal width [mm] | 800 |
| Aspect ratio | 70 |
| Tyre technology | IF |
| Direction bound | Yes |
| Tread symmetry | symmetrisch |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages,

consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.