



Hints and features:

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.

Reifen 10.0 / 75 - 15.3, AW 909 V-Line
10 PR, 123 A8, TL
BKT

Product-No.: 15711728

Technical Information:

Product number	15711728
Tyre Size	10.0 / 75 - 15.3
R / D	Diagonal
TL / TT	TL
LI / SI	123 A8
PR	10
Tread	AW 909 V-Line
Manufacturer	BKT
Recom. Rim	9.00
Width mm	274
Outer diameter mm	760
Static radius mm	343
Rolling circumference mm	2227
Payload in kg at kph (1)	1550 / 40
Inflation pressure bar	3,90
Weight kg	14,08
Stud height mm	9,0
Certified	ECE 106
Nominal width [inch]	10.0
Aspect ratio	75
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.