Bohnenkamp Moving Professionals



Hints and features:

- The Windpower WSR 75 is a truck steer tyres for local and regional transport
- It is characterized by outstanding handling under dry and wet road conditions
- The tread pattern deflects water optimally and prevents aquaplaning

Reifen 10 R 22.5, WSR 75 16 PR, 144 / 142 M, TL, 3PMSF VA, Windpower

Product-No.: 10466502

Technical Information:

Product number	10466502
Tyre Size	10 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	144 / 142 M
PR	16
Tread	WSR 75
Manufacturer	Windpower
Specification	3PMSF
Recom. Rim	7.50
Permissible rim	6.75
Width mm	252
Outer diameter mm	1022
Static radius mm	478
Rolling circumference mm	3117
Payload in kg at kph (1)	2800 / 130
Inflation pressure bar	9,00
Weight kg	48,88
Rolling resistance	D
Wet grip	В
Rolling noise DB	72
Rolling noise level	В
Stud height mm	15,0
M+S	M+S
3PMSF	3PMSF
Nominal width [inch]	10
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.