Bohnenkamp Moving Professionals



Hints and features:

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Reifen 520 / 85 R 46, TRAXION 85 158 A8 / 158 B, TL (20.8R46), Vredestein

Product-No.: 14826480

Technical Information:

Product number	14826480
Tyre Size	520 / 85 R 46
R / D	Radial
TL / TT	TL
LI / SI	158 A8 / 158 B
Tread	TRAXION 85
Manufacturer	Vredestein
Recom. Rim	DW16L
Permissible rim	DW18L
Width mm	535
Outer diameter mm	2050
Static radius mm	930
Rolling circumference mm	6150
Payload in kg at kph (1)	4250 / 40
Payload in kg at kph (2)	4250 / 50
Inflation pressure bar	1,60
Weight kg	227,6
Tyre content 75% litre	650
Stud height mm	51,0
Certified	ECE 106
Nominal width [mm]	520
Aspect ratio	85
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.