





Hints and features:

- The Vredestein Traxion Versa is an agroindustrial tyre for telescopic handlers, backhoe loaders and combine harvesters.
- Due to the shape and arrangement of its lugs, the tyre offers a flat and large contact area.
- The curved lugs are wider in the tread centre and thus enable good traction.
- Its reinforced sidewall in combination with a stabiliser ring guarantees maximum protection against tyre damages.

Reifen 500 / 70 R 24, TRAXION VERSA 164 A8 / 164 B, TL Vredestein

Product-No.: 14875060

## **Technical Information:**

Product number	14875060
Tyre Size	500 / 70 R 24
R/D	Radial
TL / TT	TL
LI/SI	164 A8 / 164 B
Tread	TRAXION VERSA
Manufacturer	Vredestein
Recom. Rim	DW16L
Permissible rim	DW15L, DW18L
Width mm	515
Outer diameter mm	1320
Static radius mm	595
Rolling circumference mm	4020
Payload in kg at kph (1)	5000 / 40
Payload in kg at kph (2)	5000 / 50
Inflation pressure bar	4,00
Weight kg	122
Tyre content 75% litre	234
Stud height mm	39,0
Certified	ECE 54
Nominal width [mm]	500
Aspect ratio	70
Direction bound	Yes
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.