



Reifen 295 / 60 R 22.5, S629
18 PR, 150 / 147 L, TL, 3PMSF
VA, Sailun

Product-No.: 11066315

Technical Information:

Product number	11066315
Tyre Size	295 / 60 R 22.5
R / D	Radial
TL / TT	TL
LI / SI	150 / 147 L
PR	18
Tread	S629
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width mm	295
Outer diameter mm	926
Rolling circumference mm	2806
Payload in kg at kph (1)	3350 / 120
Inflation pressure bar	9,00
Weight kg	52,73
Rolling resistance	C
Wet grip	B
Rolling noise DB	73
Rolling noise level	B
Stud height mm	14,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	295
Aspect ratio	60
Tread symmetry	symmetrisch

Hints and features:

- The Sailun S629 is a truck tyre for steer axles for multifunctional use in local and regional traffic.
- The optimised tread compound increases the tyre's service life.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption.
- The wide tread enables slow and even wear and good handling.
- Its wide tyre shoulder and shoulder groove design ensure low rolling resistance and low fuel consumption
- The wide tread enables slow and even wear and good handling