Bohnenkamp Moving Professionals

nokicin[®] TYRES



Hints and features:

- The Nokian E-Truck Trailer is an allseason trailer tyre.
- The pattern with zigzag-shaped grooves provides good stability and prevents damages caused by small stones.
- The robust tyre shoulder and the evenly wearing tread guarantee a long service life for the tyre.
- On top of that, the tyre is characterised by good grip on main roads, low rolling resistance and low fuel consumption.

Reifen 265 / 70 R 19.5, E-Truck Trailer 143 / 141 J, TL, 3PMSF TR, Nokian

Product-No.: 17466302

Technical Information:

Product number	17466302
Tyre Size	265 / 70 R 19.5
R / D	Radial
TL/TT	TL
LI / SI	143 / 141 J
Tread	E-Truck Trailer
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	7.50
Permissible rim	6.75, 8.25
Width mm	250
Outer diameter mm	871
Static radius mm	404
Rolling circumference mm	2648
Payload in kg at kph (1)	2725 / 100
Inflation pressure bar	8,50
Weight kg	40,8
Rolling resistance	D
Wet grip	A
Rolling noise DB	71
Rolling noise level	A
Stud height mm	13,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [mm]	265
Aspect ratio	70
Tread symmetry	symmetrisch

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Suisse AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages,

consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.