



## Hints and features:

- Hardwearing L5 tread pattern design developed for wheel loaders and wheeled bulldozers
- Excellent suitability e.g. in quarries or in the mining industry for face-working operations and work on stony, very rough ground.
- The closed tread pattern design and the high tread pattern ratio (250%) make the SR53 the best choice for use in recycling e.g. scrap yards.
- Extremely robust and cut resistant rubber compound with minor abrasion and a long service life
- Very good self-cleaning properties with stone ejection
- Important: Assembly only permitted on multi-piece wheel.

Reifen 45 / 65 R 39, Earthmax SR 53  
242 A2, TL, L5, \*\*, C.R.  
BKT

**Product-No.: 15785594**

## Technical Information:

Product number	15785594
Tyre Size	45 / 65 R 39
R / D	Radial
TL / TT	TL
LI / SI	242 A2
Tread	Earthmax SR 53
Manufacturer	BKT
Specification	L5, **, C.R.
Recom. Rim	36.00/4.5
Permissible rim	32.00/4.5
Width mm	1100
Outer diameter mm	2577
Rolling circumference mm	7747
Payload in kg at kph (1)	47500 / 10
Inflation pressure bar	6,50
Weight kg	2.206,4
Stud height mm	110,0
Nominal width [inch]	45
Aspect ratio	65
Star Rating	**
Tread symmetry	symmetrisch