

WINDPOWER
Get Your Job Done



Reifen 12.00 R 20, WGC 08
18 PR, 154 / 151 K, TT, 3PMSF
inkl. Schl. + WB, TR 179 A, VA/HA/TR, Windpower

Product-No.: 10468182

Technical Information:

Product number	10468182
Tyre Size	12.00 R 20
R / D	Radial
TL / TT	TT
LI / SI	154 / 151 K
PR	18
Tread	WGC 08
Manufacturer	Windpower
Specification	3PMSF, Schlauch + Wulstband
Recom. Rim	8.50
Permissible rim	8.50V, 9.0
Width mm	310
Outer diameter mm	1123
Static radius mm	520
Rolling circumference mm	3425
Payload in kg at kph (1)	3750 / 110
Inflation pressure bar	8,30
Weight kg	89,5
Rolling resistance	C
Wet grip	B
Rolling noise DB	74
Rolling noise level	B
Stud height mm	17,5
Certified	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Nominal width [inch]	12.00
Tread symmetry	symmetrisch

Hints and features:

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.